

TECHNICAL INFORMATION SHEET

PAR1005 Hampstead Oak

Parquet Collection



Product Information

| | |
|---------------------|---------------------|
| Product Name | Hampstead Oak |
| Product Code | PAR1005 |
| Collection | Parquet |
| Construction | Engineered |
| Size | 11 x 70 x 500mm |
| Pack Size | 1.68m ² |
| Grade | Select |
| Surface | Smooth |
| Finish | Natural Oil Protect |
| Profile | T&G |
| Edge | Square Edge |
| Pattern | Block |
| Thickness | 11mm |
| Width | 70mm |
| Length | 500mm |
| Wear Layer | 3.6mm |
| Backing | Spruce Staves |
| Top Layer | Oak |

Technical Information

| | |
|------------------------------------|-------------------------------|
| Formaldehyde Emissions | E1 |
| Pentachlorophenol Emissions | Not Detectable |
| Thermal Conductivity | RT = 0,078 m ² K/W |
| Slip Resistance | R10 |
| Fire Classification | Cfl-s1 (fully glued down) |
| Moisture Content | 7% (+/-2%) |
| Hardness Rating | 34-41H |

Additional Information

| | |
|------------------------|-----|
| UKTR Compliance | Yes |
|------------------------|-----|

Grading Information

Select grade is likely to contain some boards that have a higher number of knots than Prime, and you should also expect some of these knots to be larger in size. There is a possibility of some sapwood and small cracks and filler are likely to be present. A greater level of colour variation in the timber is to be expected.

Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions that can be found on our website.

Installation Method

| | |
|---------------------------|-----|
| Floated | No |
| Secret Nailed | No |
| Stuck Down | Yes |
| Underfloor Heating | Yes |

Recommended Care and Maintenance Products*

| | |
|--------------------------|---------------------------------------------------------|
| For Regular Care | WOCA Natural Soap |
| For Monthly Care | WOCA Oil Refresher Soap |
| Every 6-12 Months | WOCA Maintenance Gel & WOCA Intensive Cleaner as primer |

*Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.