TECHNICAL INFORMATION SHEET

PAR3005 Harrow Oak
Parquet Collection

Technical Information

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	<0.1ppm
Thermal Conductivity	0.11 m²K/W
Slip Resistance	81
Fire Classification	Cfl-s1
Moisture Content	8% (+/-2%)

Product Information

Product Name	Harrow Oak
Product Code	PAR3005
Collection	Parquet
Construction	Engineered
Size	20 x 100 x 500mm
Pack Size	0.5m²
Grade	Rustic
Surface	Smooth
Finish	Lacquered
Profile	T&G
Edge	Bevelled
Pattern	Block
Thickness	20mm
Width	100mm
Length	500mm
Wear Layer	6mm
Backing	Birch Plywood
Top Layer	Oak

Additional Information

Responsible Certification	FSC® Mix
UKTR Compliance	Yes

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as many levels of natural colour variation in the timber to be expected. A varying amount of sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fittings instructions that can be found on our website.

Installation Method

Floated	No
Secret Nailed	No
Stuck Down	Yes
Underfloor Heating	Yes

Recommended Care and Maintenance Products*

For Regular Care	WOCA Master Cleaner
For Annual Care	WOCA Master Care & WOCA Intensive Cleaner as primer

*Remember to patch test any cleaning or finishing products before using on the whole length of your floor.